

**CBS-71AC**  
**Single 6.0 Gallon Coffee Brewer**  
**High-Volume Brewing**

*Single brewer and one 6.0 gallon On-The-Go mobile LUXUS® dispenser. FETCO® is committed to designing equipment that is operator-friendly to increase safety, minimize training and increase productivity.*



**Adjustable Programming Parameters:**

- Brew Temperature
- Brew Wait
- Bypass Percent
- Drip Delay
- Brew Orifice Size\*

\*Non-standard brew orifice sizes must be ordered from FETCO®

**CBS-71AC** with LBD-6C dispenser

Model	Gallons/Hr	Oz/Hr	8 oz Cups/Hr	12 oz Cups/Hr	16 oz Cups/Hr	20 oz Cups/Hr
CBS-71AC	18.0-30.0	2,304-3,840	288-480	192-320	144-240	115-192

## Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	1.5	20-75

## Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
78	18	35	261	313

## Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour <small>cold water</small>
C71018	3x5.0 KW	120/208	3	4+G	11.5	33.0	3.0
		120/220			13.3	36.0	3.3
		120/240			15.2	37.9	3.6
C71028	3x10 KW	120/208	3	4+G	22.7	64.3	4.5
		120/220			26.3	70.3	4.8
		120/240			30.2	74.0	5.0
C71038	3X10 KW	120/480	3	3+G(1)	30.2	37.9	5.0
*C71058	3X5.0 KW	220/240	3	4+G	12.9	33.9	3.6
*C71068	3X10 KW	240/415	3	4+G	25.6	67.3	5.0

(1) Plus 120V cord and plug  
 \*EXPORT ONLY

