www.bianchivending.com

USER INTERFACE

- . SELECTION PANEL WITH 8 BACKLIGHTED BUTTONS THAT CAN BE SET EITHER AS DIRECT SELECTIONS OR PRE-SELECTIONS AND 2x16 ALPHANUMERIC LCD DISPLAY.
- . THE FRONT PANEL OFFERS EXCELLENT BRANDING OPPORTUNITIES.
- . END SELECTION ACOUSTIC SIGNAL.
- . 32 DIGIT ALPHANUMERIC DISPLAY.
- . 170 MM HIGH DELIVERY AREA SUITABLE FOR MUG OR JUG AND FOLDAWAY ESPRESSO CUP SUPPORT.



TECHNOLOGY



LED, LOW VOLTAGE LIGHTING



PATENTED ESPRESSO GROUP

EXTREMELY VERSATILE, IT IS IDEAL FOR BREAKFAST AND CAN BE INSTALLED IN MANY DIFFERENT LOCATIONS SUCH AS HOTELS, RESTAURANTS, CAFETERIAS, CATERINGS, TAKEAWAYS OR OFFICES.



GAIA FRESH MILK, an automatic machine for the delivery of hot beverages, espresso coffee, and cappuccino with fresh milk.

GAIA FRESH MILK SPECIFICATIONS

ELECTRICAL SUPPLY

V 220 V 230 - 50 Hz

INTERNAL ELECTRICAL SUPPLY


All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances, the pump and the steam ventilator that are at $230 \, \text{Vac} - 50 \, \text{Hz}$

POWER SUPPLY

2.80 kW espresso version, double boiler

WATER SUPPLY

Fitting connection = 3/8" Water pressure = 0.5 - 6.5 bar



GAIA FRESH MILK ESPRESSO

- 1. COFEEE
- 2. CHOCOLATE 3. MILK OR INSTANT
- 4. FRESH MILK

VERSIONS GAIA FRESH MILK	DOUBLE BOILER WATER SYSTEM SUPPLY
COFFEE BEANS	1
INSTANT CANISTERS	2

E2S ESPRESSO

H 650 mm x W 610 mm x D 479 mm WEIGHT 70 kg

FEATURES

• Milk frothing system for cappuccino.

DIMENSIONS

- Fresh milk module with chilled chamber and boiler for steam and heating cup.
- Mixers and boiler assembly are extractable to make maintenance operations easier.
- Available in mains water supply system version.
- Liquid waste tray: 1 litre, easily extractable, with visible signal for maximum water level.
- Coffee waste tray: 60 pods with automatic block of the machine at reaching of maximum coffee waste level.
- refrigerated unit on milk module: gas R 134 A.

PRODUCT CAPACITY

 single canister
 double canister

 Coffee beans
 0.80 kg (14 lt)

 Milk
 0.55 kg (1.75 lt)
 1.40 kg (3.5 lt)

 Chocolate
 1.30 kg (1.75 lt)
 3.00 kg (3.5 lt)

Canister for fresh milk: 4 liters

ACCESSORIES KIT

- RS232 module.
- Visual Smart Programmer Speed that allows the upload of the firmware and settings and the download of the settings and audit without a PC.
- Cup stations lighting kit through by software.

ENVIRONMENT

- Backlighted door and keypad with led to reduce energy consumption and with a lifetime greater than neon.
- Backlighted keyboard with led.
- In compliance with RHOS and WEEE.



