

## Technical Specifications

Model	Height (mm)	Width (mm)	Depth (mm)	Weight (mm)	Hopper Capacity	Dispenser Capacity	Motor HP/RPM
Model B	450	210	355	11 kg	1 kg	300g	0.4/1300
Model T	560	180	290	13 kg	1 kg	600g	0.4/1300
Model S	610	180	310	13 kg	2 kg	600g	0.5/1300
MU2	650	400	400	35 kg	2 kg + 1 kg	600g + 300g	0.5/1300x2
MU3	590	540	490	45 kg	2 kg + 2 kg + 1 kg	600g + 600g + 300g	0.5/1300x3
C6	590	200	350	16 kg	1.6 kg	300g	0.25/1300
Miracle 1 Hopper	370	185	270	10 kg	500g	Programmable Measure 5g- 16g	0.4/1300
Miracle 2 Hopper	790	400	250	33 kg	2 kg + 2 kg	Programmable Measure 5g- 16g	0.4/1300x2
Filter Caf	445	205	370	18 kg	1 kg or 2 kg	No Dispenser	0.5/1300
Wall Mounted Dispenser	320	200	205	4 kg	N/A	600g	N/A
Free Standing Dispenser	360	200	310	5 kg	N/A	600g	N/A
Chocolate Dispenser	495	200	245	10 kg	N/A	600g	N/A
Deli-Low Volume	670	210	400	14 kg	2 kg	No dispenser	0.5/1300
Deli-Med Volume	740	210	400	16 kg	2 kg	No dispenser	1.3/1300
Deli-High Volume	600	210	250	22 kg	500g	No dispenser	1.3/1300
Tranquilo	470	170	350	8 kg	500g	No dispenser	0.4/1300
Heavenly	400	165	270	4 kg	500g	70g	0.15/1300

All grinders require 13 amp power supply. Blade life expectancy - 500 kg of coffee